



HOLE	DIA.	QTY.	APPLICATION
A	0.625	4	FLOOR MOUNTING
B	1.313	6	PRE-FAB CONDUIT KNOCKOUT FOR 1in CABLE (BOTH SIDES)
C	3.500	1	PRE-FAB CONDUIT KNOCKOUT FOR 3in CABLE (TOP SIDE)
D	2.375	1	PRE-FAB CONDUIT KNOCKOUT FOR 2in CABLE (TOP SIDE)
E	1.313	1	PRE-FAB CONDUIT KNOCKOUT FOR 1in CABLE (TOP SIDE)

STANDARD PRE-FAB CONDUIT KNOCKOUTS ARE SHOWN. IF ADDITIONAL CONDUIT ENTRANCES ARE REQUIRED BY USER, ENCLOSURE SHOULD BE FIELD-MODIFIED BY INSTALLER.

NOTES:

- 1) DETAIL VIEW OF INSTRUMENT PANEL IS FEATURED ON DRAWING JE0260-XX.
- 2) BATTERY CHARGER SHIPPING WEIGHT: APPROXIMATELY (1,350-1,950) lbs.
- 2) ENCLOSURE IS A NEMA-1 TYPE CABINET WITHOUT GASKETS.
- 3) ALLOW 12in (305mm) OF FREE AIR IN FRONT AND ON TOP OF CABINET FOR VENTILATION.
- 4) BOTTOM CONDUIT ENTRY IS POSSIBLE, THROUGH EXPANDED METAL UNDERSIDE.

3	E1385	102403		 THIRD ANGLE PROJECTION	TITLE SCR/SCRF SERIES BATTERY CHARGER OUTLINE: NEMA-1 STYLE-5 ENCLOSURE		
2	E1150	022603	MCT			DRAWN BY PAC 051194 APPROVED WAH 051194	
1	E0511	072401	MCT	UNLESS OTHERWISE NOTED DIMENSIONS ARE IN INCHES. TOLERANCES ARE:	DRAWING No JE0465-03	REV 3	B
0	11001	051194	WAH		SCALE NTS	PART No JE0465-03	SHEET 1 OF 1
REV	ECN No	DATE	APP				